

Group A: '002					Group B: '115					Group C: '001				
	Engine Speed	Engine Load	Mass Air Flow (G70)	Mass Air Flow (G246)		Engine Speed	Engine Load	Boost Pressure	Boost Pressure		Engine Speed	Coolant Temperatu re (G62)	Lambda Control	Lambda Control
TIME STAMP	(G28) /min	%	Bank 1 g/s	Bank 2 g/s	TIME STAMP	(G28) /min	%	(specified) mbar	(actual) mbar	TIME STAMP	(G28) /min	re (G62) -C	Bank 1 %	Bank 2 %
53.99	680	27.8	3.58	4.81	54.16	680	27.1	1000.0	1010.0	54.32	680	99.0	-1.6	-3.9
54.49	680	24.8	3.00	4.25	54.65	640	24.1	1000.0	1010.0	54.81	680	99.0	-2.3	-5.5
54.98	680	25.6	3.25	4.36	55.14	680	27.1	1000.0	1010.0	55.31	800	99.0	-3.9	-6.3
55.49	1160	50.4	18.06	20.06	55.65	1480	51.9	1000.0	1010.0	55.81	1560	99.0	-5.5	-7.0
55.98	1560	45.9	15.67	18.56	56.15	1520	46.6	1000.0	1020.0	56.31	1600	99.0	-6.3	-1.6
56.48	1920	73.7	34.53	36.61	56.64	2080	78.2	1830.0	1050.0	56.81	2240	99.0	0.8	0.8
56.98	2400	85.0	49.53	55.81	57.15	2600	89.5	1980.0	1180.0	57.31	2800	99.0	0.0	0.0
57.48	3040	106.0	78.44	83.08	57.64	3240	118.8	2120.0	1420.0	57.81	3480	99.0	0.0	0.0
57.98	3720	159.4	138.78	147.50	58.15	3960	175.2	2120.0	1660.0	58.32	4160	99.0	0.0	0.0
58.48	4480	182.7	169.75	192.42	58.64	4680	180.5	2080.0	1660.0	58.81	4920	99.0	0.0	0.0
58.98	5120	160.2	193.67	206.17	59.14	5440	134.6	1910.0	1570.0	59.31	5640	98.0	0.0	0.0
59.47	5880	124.8	190.67	208.58	59.63	6040	124.8	1910.0	1510.0	59.80	5840	98.0	0.0	0.0
59.97	5160	134.6	196.69	210.11	60.12	4640	133.1	2040.0	1610.0	60.28	4440	98.0	0.0	0.0
60.45	4560	136.1	175.58	193.83	60.61	4640	138.3	2100.0	1650.0	60.79	4720	98.0	0.0	0.0
60.96	4840	140.6	188.75	204.50	61.13	4960	139.8	2000.0	1610.0	61.29	5080	97.0	0.0	0.0
61.45	5080	173.7	190.67	211.81	61.61	5200	173.7	1960.0	1600.0	61.78	5320	97.0	0.0	0.0
61.96	5400	169.9	198.11	216.17	62.12	5480	166.9	1900.0	1560.0	62.27	5600	97.0	0.0	0.0
62.44	5680	160.9	196.03	213.67	62.61	5800	158.6	1900.0	1520.0	62.78	5880	97.0	0.0	0.0
62.94	5920	154.9	197.50	208.58	63.11	6040	152.6	1910.0	1510.0	63.28	6120	97.0	0.0	0.0
63.44	6200	149.6	204.86	216.97	63.61	6240	148.1	1900.0	1510.0	63.78	5960	96.0	0.0	0.0
63.93	5160	152.6	202.47	213.69	64.10	4480	137.6	2120.0	1660.0	64.27	4560	96.0	0.0	0.0
64.44	4600	139.1	178.33	197.97	64.61	4640	139.8	2110.0	1650.0	64.78	4720	96.0	0.0	0.0
64.94	4760	140.6	184.61	206.17	65.09	4800	140.6	2040.0	1630.0	65.25	4840	96.0	0.0	0.0
65.42	4920	139.8	196.14	211.97	65.58	4960	139.8	1990.0	1620.0	65.73	5000	97.0	0.0	0.0
65.89	5040	138.3	197.94	215.22	66.05	5080	138.3	1950.0	1590.0	66.21	5080	97.0	0.0	0.0
66.38	5120	178.2	200.28	212.17	66.55	5160	179.7	1930.0	1570.0	66.71	5240	97.0	0.0	0.0
66.88	5280	173.7	197.94	213.69	67.05	5320	172.9	1910.0	1570.0	67.22	5360	97.0	0.0	0.0
67.38	5400	170.7	196.67	215.22	67.54	5440	169.9	1880.0	1550.0	67.71	5480	97.0	0.0	0.0
67.87	5520	166.2	200.08	214.08	68.03	5480	84.2	1000.0	1640.0	68.19	5440	97.0	-3.9	-3.9
68.36	5520	10.5	16.86	18.58	68.52	5480	12.0	1000.0	1230.0	68.69	5440	97.0	1.6	1.6
68.85	5400	12.0	14.17	16.36	69.01	5400	12.0	1000.0	1120.0	69.18	5360	97.0	0.0	0.0
69.34	5320	12.8	14.72	16.11	69.50	5280	12.8	1000.0	1090.0	69.67	5200	98.0	0.0	0.0