

CWT**HUHTA SAMPO 002****CWT****INITIAL SPIN**

| LEFT SIDE | | | | 365.83 GramMm |
|-----------|--------|--------|--------------|---------------|
| Weight | RPM | Radius | Force in kg. | |
| 2.69 | 1000 | 136 | 0.41 | |
| 2.69 | 2000 | 136 | 1.63 | |
| 2.69 | 3000 | 136 | 3.68 | |
| 2.69 | 4000 | 136 | 6.55 | |
| 2.69 | 5000 | 136 | 10.23 | |
| 2.69 | 6000 | 136 | 14.73 | |
| 2.69 | 7000 | 136 | 20.05 | |
| 2.69 | 8000 | 136 | 26.19 | |
| 2.69 | 9000 | 136 | 33.15 | |
| 2.69 | 10,000 | 136 | 40.92 | |

Date Tested

3/7/2019

| RIGHT SIDE | | | | 344.56 GramMm |
|------------|--------|--------|--------------|---------------|
| Weight | RPM | Radius | Force in kg. | |
| 4.03 | 1000 | 85.5 | 0.38 | |
| 4.03 | 2000 | 85.5 | 1.54 | |
| 4.03 | 3000 | 85.5 | 3.47 | |
| 4.03 | 4000 | 85.5 | 6.16 | |
| 4.03 | 5000 | 85.5 | 9.63 | |
| 4.03 | 6000 | 85.5 | 13.88 | |
| 4.03 | 7000 | 85.5 | 18.89 | |
| 4.03 | 8000 | 85.5 | 24.67 | |
| 4.03 | 9000 | 85.5 | 31.22 | |
| 4.03 | 10,000 | 85.5 | 38.55 | |

BOBWEIGHT CARD

| | |
|------------------|------|
| Rod (Big End) | 0.00 |
| Insert | 0.00 |
| Total | 0.00 |
| Times Rods/Throw | 2 |
| Total | 0.00 |
| Oil | 0.00 |
| Rotating Weight | 0.00 |

| | | | |
|----------------------|------|-----------------|------|
| Rod (Small End) | 0.00 | | |
| Piston | 0.00 | | |
| Pins | 0.00 | | |
| Locks | 0.00 | | |
| Rings | 0.00 | | |
| Total | 0.00 | | |
| Reciprocating Weight | 0.00 | Reciprocating % | 50 |
| Reciprocating Factor | | | 0.00 |

CWT

| | | | |
|-----------|---|----------------|---|
| Bobweight | 0 | Half Bobweight | 0 |
|-----------|---|----------------|---|

CWT**FINAL SPIN**

| LEFT SIDE | | | | 339.99 GramMm |
|-----------|--------|--------|--------------|---------------|
| Weight | RPM | Radius | Force in kg. | |
| 2.5 | 1000 | 136 | 0.38 | |
| 2.5 | 2000 | 136 | 1.52 | |
| 2.5 | 3000 | 136 | 3.42 | |
| 2.5 | 4000 | 136 | 6.08 | |
| 2.5 | 5000 | 136 | 9.51 | |
| 2.5 | 6000 | 136 | 13.69 | |
| 2.5 | 7000 | 136 | 18.63 | |
| 2.5 | 8000 | 136 | 24.34 | |
| 2.5 | 9000 | 136 | 30.81 | |
| 2.5 | 10,000 | 136 | 38.03 | |

Target Tolerance
360 GramMm

| RIGHT SIDE | | | | 285.56 GramMm |
|------------|--------|--------|--------------|---------------|
| Weight | RPM | Radius | Force in kg. | |
| 3.34 | 1000 | 85.5 | 0.32 | |
| 3.34 | 2000 | 85.5 | 1.27 | |
| 3.34 | 3000 | 85.5 | 2.87 | |
| 3.34 | 4000 | 85.5 | 5.11 | |
| 3.34 | 5000 | 85.5 | 7.98 | |
| 3.34 | 6000 | 85.5 | 11.50 | |
| 3.34 | 7000 | 85.5 | 15.65 | |
| 3.34 | 8000 | 85.5 | 20.44 | |
| 3.34 | 9000 | 85.5 | 25.87 | |
| 3.34 | 10,000 | 85.5 | 31.95 | |

Job # HUHTA SAMPO 002**Engine Audi 2.7T**

Kampiakseli +hilmapyörä +vauhtipyörä +

Moottorien säädöt ja mittaukset dynamometrillä, elektroniset moottorinohjainlaitteet ja moottorien dynaamiset tasapainotukset, sekä alan osat ja tarvikkeet.

Helalantie 11, 21800 KYRÖ, (02) 5332686